

(2) Standard Vehicles.

The minimum dimensions for parking spaces and aisles for standard motor vehicles shall be as follows:

**DIMENSIONS FOR STANDARD PARKING SPACES AND AISLES**

Parking Angle	Space Width	Space Length	Aisle Width		Width at Curb
			(1-way)	(2-way)	
90°	9'	18'0"	24'0"	24'0"	9'0"
60°	9'	21'0"	18'0"	20'0"	10'5"
45°	9'	19'10"	15'0"	20'0"	12'9"
30°	9'	16'10"	12'0"	20'0"	18'0"
Parallel	8'	24'0"	12'0"	24'0"	n/a

(3) Compact Vehicles.

Up to one-third of the total number of required parking spaces may be designed for compact motor vehicles. Where possible, these spaces shall be clustered together, located in areas with convenient access to the principal building(s) served, and shall be marked with signs restricting their use to compact motor vehicles. The minimum dimensions for parking spaces and aisles for compact motor vehicles shall be as follows:

**DIMENSIONS FOR COMPACT PARKING SPACES AND AISLES**

Parking Angle	Space Width	Space Length	Aisle Width		Width at Curb
			(1-way)	(2-way)	
90°	8'	15'0"	24'0"	24'0"	8'0"
60°	8'	16'8"	18'0"	20'0"	9'3"
45°	8'	16'6"	15'0"	20'0"	11'4"
30°	8'	14'0"	12'0"	20'0"	16'0"
Parallel	7'	21'0"	12'0"	24'0"	n/a

Aisle widths refer to that portion of the parking area required for ingress and egress to parking spaces. Other areas of access must meet the width dimensions required for driveways. All required handicapped parking spaces must be designed in accordance with requirements of the Building Code.

**STANDARD SPACES**

